









Specifications

Description	>99% Silver Knight bacteria destroyed Fitness		Elite	Stamina
Surface	-	Silver Knight	TECH Surface	TECH Surface
Backing	-	Closed cell PVC foam	Closed cell double foam	Compact backing
Thickness	EN 428	5 mm	6 mm	2 mm
Weight	EN 430	3,6 kg/m²	3,7 kg/m²	2,8 kg/m²
Width	EN 426	2 m	2 m	2 m
Standard roll length	EN 426	15 m ± 10%	15 m ± 10%	20 m ± 10%
Maximal roll length	EN 426	25 m	25 m	25 m

Classification

Product specification		EN 651 Vinyl floor covering for indoor sport purposes Meets the requirement of EN 14904 on a sub-construction		Vinyl indoor sport floor EN 14904 (category P1)	EN 649 Vinyl floor covering for indoor sport purposes Meets the requirement of EN 14904 on a sub-construction
Disinfection	ISO 27447	99% bacteria destroyed		-	-
Bacteria resistance	ISO 846	resistant to bacteria		resistant to bacteria	resistant to bacteria
Impact sound insulation	EN IS0717-2	17 dB		21 dB	-
Thermal resistance	-	0,04 m² K/W		0,06 m ² K/W	0,01 m ² K/W
Reaction to fire	EN 13501	C _{fl} -s1		C _{ff} -s1	C _{ff} -s1
Formaldehyde emission	-	No formaldehyde		No formaldehyde	No formaldehyde
Pentachlorphenol	-	No pentachlorphenol		No pentachlorphenol	No pentachlorphenol

Sport properties

Friction	EN 13036-4	80-110	80-110	80-110
Shock absorption	EN 14808	-	27 %	-
Vertical deformation	EN 14809	-	1,0 mm	-
Ball rebound	EN 12235	99 %	99 %	99 %
Specular gloss	EN 2813	< 30	< 30	< 30

Technical characteristics

Dimensional stability	EN 434	± 0,2 %	± 0,2 %	± 0,2 %
Indentation resistance	EN 1516	0,13 mm	0,44 mm	0,23 mm
Resistance to rolling load	EN 1569	1500 N	1500 N	1500 N
Colour fastness	ISO 105 B02	6	6	6
Chemical resistance	EN 423	no change	no change	no change
Abrasion resistance	EN ISO 5470-1	< 250 mg/1000cycles	< 250 mg/1000cycles	< 250 mg/1000cycles

Recommendation		AERC	BICS	CARDIO	STRENGHT
		body-art, callanetics kickbox aerobic, pilates, slide yoga, zumba	kangoo, spinning step-aerobic	TRAININGS	TRAININGS
_	Silver Knight Fitness	00	••	00	
	Elite	**	**	_	_
	Stamina	_	-		00

Product benefits



Our products are made by technological procedures without using solvents or heavy metals – less environmental impact



No polish required – reduced maintenance costs and energy consumption



GraboSAN treatment stops the growth of germs – reduced risk of contamination in case of injuries



Available in rolls - easy and quick installation 200 cm width of roll less welding



High energy absorption due to the lower











Graboplast Floor Covering Manufacturers Ltd. H-9023 Győr, Fehérvári út. 16/b. Telefon: (+36) 96 506-132

www.graboplast.hu